

CONFIX™ WST split cable protection conduits

for cables with connectors



RoHS
compliant

REACH
COMPLIANCE

Made in
Germany

The CONFIX™ WST is a two piece corrugated conduit. Perfect for routing cables with or without connectors in rough environments.

In conjunction with e.g. [KVT-W90](#), a high degree of flexibility is achieved. Numerous conduit sizes can be used thanks to the wide variety of [split grommets](#) offered.

The length of the CONFIX™ WST split corrugated conduit can be customized to your application.

Defining your individual length:

Order numbers (ex.):

Length = 1.500 mm --> Order No. 31200.01500

All conduits are available by the metre (0.5 m steps).

Specifications

Material	Polypropylene
Operating temperature	-40 C° to 105 C°
Properties	UV-resistant

Advantages & benefits

■ Retrofits, repairs and maintenance can be done much more easily and quickly

Product types & sizes

CONFIX™ WST NW 10



Part No.	31200.xxxxx
EAN	
Package quantity	1
Nominal size	NW 10
External diameter	13,6 mm
Internal diameter	8,7 mm
Bending radius (static)	25 mm

CONFIX™ WST NW 14



Part No. **31210.xxxxx** Compatible with CONFiX **31410,**
EAN **31411**
Package quantity **1** FWS
Nominal size **NW 14**
External diameter **18,5 mm**
Internal diameter **12,5 mm**
Bending radius **35 mm**
(static)

CONFIX™ WST NW 16



Part No. **31215.xxxxx** Compatible with CONFiX **31413,**
EAN **31414**
Package quantity **1** FWS
Nominal size **NW 16**
External diameter **21,5 mm**
Internal diameter **16 mm**
Bending radius **40 mm**
(static)

CONFIX™ WST NW 20

Part No. **31220.xxxxx**
EAN
Package **1**
quantity
Nominal size **NW 20**
External diameter **25,5 mm**
Internal diameter **19,5 mm**
Bending radius **45 mm**
(static)



CONFIX™ WST NW 23

Part No. **31230.xxxxx** Compatible with CONFIX **31416,**
EAN **31417**
Package **1** FWS
quantity
Nominal size **NW 23**
External diameter **31 mm**
Internal diameter **24,2 mm**
Bending radius **50 mm**
(static)



CONFIX™ WST NW 29



Part No. **31235.xxxxx** Compatible with CONFiX **31419, 31420**
EAN
Package quantity **1** FWS
Nominal size **NW 29**
External diameter **35,5 mm**
Internal diameter **27,3 mm**
Bending radius **90 mm**
(static)

CONFIX™ WST NW 37



Part No. **31240.xxxxx** Compatible with CONFiX **31422, 31423**
EAN
Package quantity **1** FWS
Nominal size **NW 37**
External diameter **41,4 mm**
Internal diameter **31 mm**
Bending radius **110 mm**
(static)

CONFiX™ WST NW 45

Part No.	31250.xxxxx	Compatible	31425,
EAN		with CONFiX	31426
Package	1	FWS	
quantity			
Nominal size	NW 45		
External diameter	54 mm		
Internal diameter	42,7 mm		
Bending radius	130 mm		
(static)			



CONFiX™ WST NW 70

Part No.	31260.xxxxx		
EAN			
Package	1		
quantity			
Nominal size	NW 70		
External diameter	79,8 mm		
Internal diameter	66,5 mm		
Bending radius	190 mm		
(static)			



